S.,

Aluminium alloys ingots for remelting

ALLOY DATA SHEET

ALLOY GROUP ¹		NUMERICAL DESIGNATION ¹				CHEMICAL DESIGNATION ¹					S.A.V. ALLOY CODE			
AI	Si5Cu		EN /	AB -	45500)	EN	AB-A	I Si7C	u0,5N	Лg	01012568		
								,	lloyed ingots		,	tions		
					NGOT	S CHE	MIC	AL CO	MPOS	ITION			Other	Other
Alloy	% _{wt}	Si	Fe	Cu	Mn	Mg	Cr	Ni	Zn	Pb	Sn	Ti	Each	Total
,														
EN AB -	Min.	6,5	-	0,2	-	0,25	-	-	-	-	-	-	-	-

	CASTINGS CHEMICAL COMPOSITION													
Alloy	% wt	Si	Fe	Cu	Mn	Mg	Cr	Ni	Zn	Pb	Sn	Ti	Other Each	Other Total
EN AC -	Min.	6,5	-	0,2	-	0,20	-	-	-	-	-	-	-	-
45500 ²	Max	7,5	0,25	0,7	0,15	0,45	-	-	0,07	-	-	0,20	0,03	0,10
			2 F	N 1706-20	20 Aluminiun	n and alumin	ium allovs	- Castings	- Chemical c	omnosition a	and mechani	cal properties		

MEC	HANICA	D D D D	

Minimum mechanical properties for separately cast sample										
Casting method	Temper designation	Tensile strength <i>R_m [MPa] min.</i>	Yield strength R _{p0,2} [MPa] min	Elongation A [%] min	Brinnell hardness HBW min					
Sand Casting	Т6	250	190	1	85					
Chill Casting	Т6	320	240	4	100					
Low Pressure die Casting	Т6	320	240	4	100					
Investment Casting	-	-	-	-	-					
Pressure die Casting	-	-	-	-	-					
Potential mechanical properties of test specimens from castings ³	_4	310	260	5	100					

²EN 1706:2020 Aluminium and aluminium alloys – Castings – Chemical composition and mechanical properties ³It cannot be assumed that the given values can be reached throughout the casting since mechanical properties strongly depend on the solidification rate, the heat treatment and the soundness of the casting. Therefore, the values and the position of the area where those values can be achieved shall be agreed between supplier and customer. ⁴ The heat treatment has to be defined according to the type of casting produced.

		PH۱	SICAL P	RO	PERTIES ²				
۵	SAND CASTING		•		MACHIN	MACHINABILITY IN THE AS CAST STATE			
МЕТНО	PERMANENT MOULD CASTIN	>		MACHINA	MACHINABILITY AFTER HEAT TREATMENT				
CASTING METHOD	PRESSURE DIE CASTING	-		RE	SISTANCE TO CO	RROSION	B/C		
CA	INVESTMENT CASTING	INVESTMENT CASTING			DECORATIVE ANODIZING			D	
~	FLUIDITY	В	OTHER PROPERTIES		ABILITY TO BE WELDED				
CASTABILITY	RESISTANCE TO HOT TEARIN	В	THER PI		ABILITY TO BE POLISHED				
CAS'	PRESSURE TIGHTNESS	В	6	LIN	LINEAR THERMAL EXPANSION [10 ^{.6} /K] (293 K-373 K)				
TIES	STRENGTH AT ROOM TEMPERA	IGTH AT ROOM TEMPERATURE			ELEC	TRICAL CONDUCT	[IVITY [MS/m]	16 - 22	
MECHANICAL PROPERTIES	STRENGTH AT HIGH TEMPERAT 200 °C	В			THERMAL CONDUCTIVITY [W/(m K)]				
NICAL	DUCTILITY (SHOCK RESISTAN	CE)	A/B						
MECHA	FATIGUE RESISTANCE [MPA]	80 - 110							
✔ Inc	 Indicates the most commonly casting process used for each alloys A: Optimal 				C: D: E: Fair Poor Not Recommended			F: Unsuitable	
	² EN 1706:2020 A	luminium and alum	inium alloys – Cast	tings –	Chemical composition	and mechanical prop	erties		

S.A.V. S.p.A. Società Alluminio Veneto REGISTERED OFFICE: VIA COLOMBO, 5 35010 TREBASELECHE (PD) ITALY TEL. +39 049 3938101 FAX 049 3938728 E-MAIL : <u>info@sav-al.com</u> WEB: www.sav-al.com Page 1/2

COMPANY WITH MANAGEMENT SYSTEM CERTIFIED = ISO 9001 = = IATF 16949 = COMPANY WITH MANAGEMENT SYSTEM CERTIFIED = ISO 14001 = = ISO 45001 = = ISO 50001 =

VERIFIED ENVIRONMENTAL MANAGEMENT EMAS IT-00184 S.A.V. S.p.A Società Alluminio Veneto

Aluminium alloys ingots for remelting

	HEAT TREATMENT DESIGNATION ²							
ABBREVIATION	HEAT TREATMENT							
F	AS CAST							
0	ANNEALED							
T1	CONTROLLED COOLING FROM CASTING AND NATURALLY AGED							
T4	SOLUTION HEAT TREATED AND NATURALLY AGED WHERE APPLICABLE							
T5	CONTROLLED COOLING FROM CASTING AND ARTIFICIALLY AGED OR OVER-AGED							
T6	SOLUTION HEAT TREATED AND ARTIFICIALLY AGED							
T64	SOLUTION HEAT TREATED AND ARTIFICIALLY UNDER-AGED							
T7	SOLUTION HEAT TREATED AND ARTIFICIALLY OVER-AGED (STABILIZED)							
	² EN 1706:2020 Aluminium and aluminium alloys – Castings – Chemical composition and mechanical properties							

	CORRELATION WITH OTHER STANDARDS EN AB - 45500 / EN AC - 45500											
NATION		U.S.A. JAPAN		INTERNATIONAL	ITALY	FRANCE	GERMANY	GREAT BRITAIN				
STA	NDARD	B179	H2211	211 17615		NF A57-702	1725	BS 1490				
ST.	ATUS	ACTIVE	ACTIVE	ACTIVE	SUPERSEDED	SUPERSEDED	SUPERSEDED	SUPERSEDED				
IDENTICAL STANDARD	INGOT SPECIFICATION	-	-	-	-	-	-	-				
SIMILAR STANDARD	INGOT SPECIFICATION	-	-	-	-	-	-	-				

Any dissemination, copy or reproduction of this document, even if only for extract, is prohibited.

The physical and mechanical properties shown in this data sheet have a mere informative purpose since they are detected on sample cast separately in specific cooling conditions. No liability is accepted for decisions based on the indicated physical and mechanical properties and no guarantee is given for the physical and mechanical properties indicated, as they depend on the specific conditions of casting of the cast pieces.

S.A.V. S.p.A. Società Alluminio Veneto REGISTERED OFFICE: VIA COLOMBO, 5 35010 TREBASELECHE (PD) ITALY TEL. +39 049 9387191 FAX 049 9387828 E-MAIL : info@sav-al.com WEB: www.sav-al.com Page 2/2

COMPANY WITH MANAGEMENT SYSTEM CERTIFIED

= ISO 9001 = = IATF 16949 = COMPANY WITH MANAGEMENT SYSTEM CERTIFIED = ISO 14001 = = ISO 45001 = = ISO 50001 =

VERIFIED ENVIRONMENTAL MANAGEMENT EMAS IT-00184