

S.A.V. S.p.A Società Alluminio Veneto

Aluminium alloys ingots for remelting

ALLOY DATA SHEET

ALLOY	NUMERICAL	CHEMICAL	S.A.V. ALLOY
GROUP ¹	DESIGNATION ¹	DESIGNATION ¹	CODE
AlSi9Cu	EN AB - 46300	EN AB-Al Si7Cu3Mg	01013208

¹EN 1676:2020 Aluminium and aluminium alloys – Alloyed ingots for remelting – Specifications

	INGOTS CHEMICAL COMPOSITION													
Alloy	% wt	Si	Fe	Cu	Mn	Mg	Cr	Ni	Zn	Pb*	Sn	Ti	Other Each	Other Total
EN AB -	Min.	6,5	-	3,0	0,20	0,35	-	-	-	-	-	-	-	-
46300 ¹	Max	8,0	0,7	4,0	0,65	0,60	-	0,30	0,65	0,15	0,10	0,20	0,05	0,25
	¹ EN 1676:2020 Aluminium and aluminium alloys – Alloyed ingots for remelting – Specifications. * The Alloy produced by S.A.V. S.p.A. has a lead content less than 0.1%													

CASTINGS CHEMICAL COMPOSITION														
Alloy	Alloy % _{wt} Si Fe Cu Mn Mg Cr Ni Zn Pb [*] Sn Ti Each Total													
EN AC -	Min.	6,5	-	3,0	0,20	0,30	-	-	-	-	-	-	-	-
46300 ²	Max	8,0	0,8	4,0	0,65	0,60	-	0,30	0,65	0,15	0,10	0,25	0,05	0,25

²EN 1706:2020 Aluminium and aluminium alloys – Castings – Chemical composition and mechanical properties. * The Alloy produced by S.A.V. S.p.A. has a lead content less than 0,1%

MECHANICAL PROPERTIES² Minimum mechanical properties for separately cast sample **Brinnell hardness** Temper Tensile strength Yield strength Elongation **Casting method HBW** min R_m [MPa] min. R_{p0,2} [MPa] min A [%] min designation Sand Casting **Chill Casting** 180 100 1 80 Low Pressure die Casting F 180 100 1 80 **Investment Casting** Pressure die Casting Potential mechanical properties of 225 180 1 85 test specimens from castings3

²EN 1706:2020 Aluminium and aluminium alloys – Castings – Chemical composition and mechanical properties

3lt cannot be assumed that the given values can be reached throughout the casting since mechanical properties strongly depend on the solidification rate, the heat treatment and the soundness of the casting. Therefore, the values and the position of the area where those values can be achieved shall be agreed between supplier and customer. ⁴ The heat treatment has to be defined according to the type of casting produced.

		PHY	SICAL P	RO	PERTIES ²						
D	SAND CASTING		_		MACHIN	MACHINABILITY IN THE AS CAST STATE					
ИЕТНО	PERMANENT MOULD CASTIN	~		MACHINA	ABILITY AFTER HE	AT TREATMENT	-				
CASTING METHOD	PRESSURE DIE CASTING	_		RE	SISTANCE TO CO	RROSION	D				
Ç	INVESTMENT CASTING	_	IES		DECORATIVE ANODIZING						
,	FLUIDITY	В	PROPERTIES		В						
CASTABILITY	RESISTANCE TO HOT TEARII	В	OTHER PI		ABILITY TO BE POLISHED						
CASI	PRESSURE TIGHTNESS	В	6	LIN	LINEAR THERMAL EXPANSION [10°/K] (293 K-373 K)						
TES	STRENGTH AT ROOM TEMPERA	TURE	D		ELEC	TRICAL CONDUCT	FIVITY [MS/m]	14 - 17			
PROPERT	STRENGTH AT ROOM TEMPERATURE STRENGTH AT HIGH TEMPERATURE 200 °C					THERMAL CONDUCTIVITY [W/(m K)]					
MECHANICAL	DUCTILITY (SHOCK RESISTAN	С									
MECH/	FATIGUE RESISTANCE [MPA]	60 - 90									
✓ In	✓ Indicates the most commonly casting process used for each alloys A: Optimal			C: D: E: Fair Poor Not Recommended				F: Unsuitable			
² EN 1706:2020 Aluminium and aluminium alloys – Castings – Chemical composition and mechanical properties											

Page 1/2

= ISO 14001 = = ISO 45001 = = ISO 50001 =

VERIFIED ENVIRONMENTAL MANAGEMENT **EMAS** IT-00184



S.A.V. S.p.A Società Alluminio Veneto

Aluminium alloys ingots for remelting

HEAT TREATMENT DESIGNATION ²								
ABBREVIATION	HEAT TREATMENT							
F	AS CAST							
0	ANNEALED							
T1	CONTROLLED COOLING FROM CASTING AND NATURALLY AGED							
T4	SOLUTION HEAT TREATED AND NATURALLY AGED WHERE APPLICABLE							
T5	CONTROLLED COOLING FROM CASTING AND ARTIFICIALLY AGED OR OVER-AGED							
T6	SOLUTION HEAT TREATED AND ARTIFICIALLY AGED							
T64	SOLUTION HEAT TREATED AND ARTIFICIALLY UNDER-AGED							
T7	SOLUTION HEAT TREATED AND ARTIFICIALLY OVER-AGED (STABILIZED)							
	² EN 1706:2020 Aluminium and aluminium alloys – Castings – Chemical composition and mechanical properties							

CORRELATION WITH OTHER STANDARDS EN AB - 46300 / EN AC - 46300											
NATION U.S.A. JAPAN INTERNATIONAL ITALY FRANCE GERMANY											
STANDARD	B179	H2211	17615	UNI	NF A57-702	1725	BS 1490				
STATUS	ACTIVE	ACTIVE	ACTIVE	SUPERSEDED	SUPERSEDED	SUPERSEDED	SUPERSEDED				
IDENTICAL INGOT STANDARD SPECIFICATION	-	-	Al Si7Cu3Mg	-	-	-	-				
SIMILAR INGOT STANDARD SPECIFICATION	-	AC2B	-	7369	A-S7U3G	GB-ALSi6Cu4 – 225	-				

Any dissemination, copy or reproduction of this document, even if only for extract, is prohibited.

The physical and mechanical properties shown in this data sheet have a mere informative purpose since they are detected on sample cast separately in specific cooling conditions. No liability is accepted for decisions based on the indicated physical and mechanical properties and no guarantee is given for the physical and mechanical properties indicated, as they depend on the specific conditions of casting of the cast pieces.