

## S.A.V. S.p.A Società Alluminio Veneto

Aluminium alloys ingots for remelting

#### **ALLOY DATA SHEET**

ALLOY	NUMERICAL	CHEMICAL	S.A.V. ALLOY
GROUP <sup>1</sup>	DESIGNATION <sup>1</sup>	DESIGNATION <sup>1</sup>	CODE
AlSi9Cu	EN AB - 46600	EN AB-Al Si7Cu2	01012210

<sup>1</sup>EN 1676:2020 Aluminium and aluminium alloys – Alloyed ingots for remelting – Specifications

	INGOTS CHEMICAL COMPOSITION													
Alloy	% wt	Si	Fe	Cu	Mn	Mg	Cr	Ni	Zn	Pb⁺	Sn	Ti	Other Each	Other Total
EN AB -	Min.	6,0	-	1,5	0,15	-	-	-	-	-	-	-	-	-
46600 <sup>1</sup>	Max	8,0	0,7	2,5	0,65	0,35	-	0,35	1,0	0,25	0,15	0,20	0,05	0,15
	<sup>1</sup> EN 1676:2020 Aluminium and aluminium alloys – Alloyed ingots for remelting – Specifications.  * The Alloy produced by S.A.V. S.p.A. has a lead content less than 0,1%.													

	CASTINGS CHEMICAL COMPOSITION													
Alloy % wt Si Fe Cu Mn Mg Cr Ni Zn Pb* Sn Ti Other Other Each Total														
EN AC -	Min.	6,0	-	1,5	0,15	-	-	-	-	-	-	-	-	-
46600 <sup>2</sup>	Max	8,0	0,8	2,5	0,65	0,35	-	0,35	1,0	0,25	0,15	0,25	0,05	0,15
	<sup>2</sup> FN 1706-2020 Aluminium and aluminium alloys – Castings – Chemical composition and mechanical properties													

\* The Alloy produced by S.A.V. S.p.A. has a lead content less than 0,1%

#### **MECHANICAL PROPERTIES<sup>2</sup>** Minimum mechanical properties for separately cast sample

Casting method	Temper Tensile strength Yield strength designation $R_m$ [MPa] min. $R_{p0,2}$ [MPa] min		Elongation A [%] min	Brinnell hardness HBW min	
Sand Casting	F	150	90	1	60
Chill Casting	F	170	100	1	75
Low Pressure die Casting	F	170	100	1	75
Investment Casting	-	-	-	-	-
Pressure die Casting	-	-	-	-	-
Potential mechanical properties of test specimens from castings <sup>3</sup>	-	-	-	-	-

<sup>2</sup>EN 1706:2020 Aluminium and aluminium alloys – Castings – Chemical composition and mechanical properties

3/1t cannot be assumed that the given values can be reached throughout the casting since mechanical properties strongly depend on the solidification rate, the heat treatment and the soundness of the casting. Therefore, the values and the position of the area where those values can be achieved shall be agreed between supplier and customer.c

PHYSICAL PROPERTIES <sup>2</sup>										
	SAND CASTING		<b>~</b>		MACHIN	В				
МЕТНО	PERMANENT MOULD CASTIN	~		MACHINA	ABILITY AFTER HE	AT TREATMENT	-			
CASTING METHOD	PRESSURE DIE CASTING	_		RE	SISTANCE TO CO	RROSION	D			
investment casting			_	TIES		DECORATIVE ANODIZING				
FLUIDITY			В	OTHER PROPERTIES		ABILITY TO BE WELDED				
rabilit	RESISTANCE TO HOT TEARING  PRESSURE TIGHTNESS			THER P		ABILITY TO BE PO	С			
CAS				Б	LIN	IEAR THERMAL E [10-6/K] (293 K-3		21,00		
IES	STRENGTH AT ROOM TEMPERA	TURE	D		ELEC	ELECTRICAL CONDUCTIVITY [MS/m]				
PROPERT	STRENGTH AT HIGH TEMPERATURE 200 °C					THERMAL CONDUCTIVITY [W/(m K)]				
ANICAL	STRENGTH AT ROOM TEMPERATURE  STRENGTH AT HIGH TEMPERATURE  200 °C  DUCTILITY (SHOCK RESISTANCE)  FATIGUE RESISTANCE  [MPA]									
MECH										
✓ In	✓ Indicates the most commonly casting process used for each alloys  A: Optimal				C:         D:         E:           Fair         Poor         Not Recommend		E: Not Recommended	F: Unsuitable		
	<sup>2</sup> EN 1706:2020 A	luminium and alumi	inium alloys – Cast	tings –	Chemical composition	and mechanical prop	erties			

Page 1/2

IT-00184



# S.A.V. S.p.A Società Alluminio Veneto

### Aluminium alloys ingots for remelting

HEAT TREATMENT DESIGNATION <sup>2</sup>								
ABBREVIATION	HEAT TREATMENT							
F	AS CAST							
0	ANNEALED							
T1	CONTROLLED COOLING FROM CASTING AND NATURALLY AGED							
T4	SOLUTION HEAT TREATED AND NATURALLY AGED WHERE APPLICABLE							
T5	CONTROLLED COOLING FROM CASTING AND ARTIFICIALLY AGED OR OVER-AGED							
T6	SOLUTION HEAT TREATED AND ARTIFICIALLY AGED							
T64	SOLUTION HEAT TREATED AND ARTIFICIALLY UNDER-AGED							
T7	SOLUTION HEAT TREATED AND ARTIFICIALLY OVER-AGED (STABILIZED)							
	<sup>2</sup> EN 1706:2020 Aluminium and aluminium alloys – Castings – Chemical composition and mechanical properties							

	CORRELATION WITH OTHER STANDARDS  EN AB - 46600 / EN AC - 46600												
NAT	ΓΙΟΝ	U.S.A. JAPAN		INTERNATIONAL	ITALY	FRANCE	GERMANY	GREAT BRITAIN					
STAN	STANDARD		H2211	17615	UNI	NF A57-702	1725	BS 1490					
STA	TUS	ACTIVE	ACTIVE	ACTIVE	SUPERSEDED	SUPERSEDED	SUPERSEDED	SUPERSEDED					
IDENTICAL STANDARD	INGOT SPECIFICATION	-	-	Al Si7Cu2	-	-	-	-					
SIMILAR STANDARD	INGOT SPECIFICATION	328.1	AC4B	-	7369	-	-	LM27					

Any dissemination, copy or reproduction of this document, even if only for extract, is prohibited.

The physical and mechanical properties shown in this data sheet have a mere informative purpose since they are detected on sample cast separately in specific cooling conditions. No liability is accepted for decisions based on the indicated physical and mechanical properties and no guarantee is given for the physical and mechanical properties indicated, as they depend on the specific conditions of casting of the cast pieces.